


FIBER OPTIC TERMINATION BOX

SPDF-O8SCS-PMHPA



General Description

This box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTx network building.

Features

- Total enclosed structure, be in nice shape
- Protects and manages cable effectively
- Secured with anti-theft locking mechanism
- Standard size, light weight
- High quality PC +ABS material
- Good properties of dust, and moisture proofing, IP65
- Clamping for feeder cable and drop cable, fiber splicing, fixation, storage, distribution...etc all in one
- Suitable for SC and LC duplex adaptor and pigtail
- Easy to operate
- Suitable for both outdoor and indoor use

Application

- Telecommunication subscriber loop
- Fiber to the home(FTTH)
- LAN/WAN


Technical Data

Item	Parameter
Model No.	SPDF-O8SCS-PMHPA
Mounting way	Wall-mounting or Pole mounting
Work Temperature	-40 °C ~+85 °C
Relative Humidity	≤ 85% (+30 °C)
Atmospheric Pressure	70Kpa~106Kpa
Insert Loss	≤ 0.2dB
UPC Return Loss	≥ 50dB
APC Return Loss	≥ 60dB
Insert and Pull out Life	≥ 1000 times
Insulation	The grounding device is insulated with the Termination box, IR ≥1000m Ω/500V (direct current)
Withstand Voltage	Between the grounding device and the box body, the withstand voltage is over 3000V/Min, no breakdown and flash over. U ≥3000V (direct current)

Dimensions& Installation Dimensions

Dimensions


223mmx 180mmx48mm




Type 1

Installation Dimensions

120mm x 80mm





Ordering information

Part Number	Product Description
SPDF-O8SCS-PMHPA	Splitter Distribution Box Outdoor pole mounted 8 cores Simplex SC/Duplex LC type available for Steel tube splitter installation with hoop ,without adaptors , pigtails and splitter Plastic type A

E-mail: sales@sopto.com

Web : <http://www.sopto.com>